



BILATERAL DAMPER SYSTEM

SPHERICAL BEARING

Global patented spherical bearings with up to 30% angle adjustability, alleviate the damage caused by uneven foundation settlement during operations. The spherical bearings dissipate the extra stress caused by the deformation of the tracker system, thus reduce the load and failure rate of each component.

TECHNICAL SPECIFICATIONS

GENERAL FEATURES

Wind and snow loads tolerance

Design wind speed 55 m/s (This value depends on project conditions)

STRUCTURE

Material High Yield Strength Steel

Coating HDG, Pregalvanizide & ZM⁽³⁾

CONTROLLER

Electronic board with microprocessor

IP65

Customizable

Cup / Ultrasonic

Configurable

Wired option: RS 485

Wireless option: LoRa/Zigbee

Altitude < 4000 m⁽⁵⁾

Temperature: -30~60°C⁽⁵⁾

Digital inclinometer

DC motor: 0.15 kW

Grid connection 3295a1.5ts (iWARRANTYes15 (on)20ast

WARRANTY

Warranty period of 10 years for the structural set of elements which build the tracker up and have been supplied by Trina Solar.

Warranty period of 5 years for commercial components (including but not limited to drive system ,electrical system, bearing set, fasteners, etc.)

*1 Depending on layout

*2 For scenarios beyond the scope of use, please consult TrinaTracker

*3 Standard configuration, Other coating under request, please consult TrinaTracker

*4 Includes smart tracking algorithm and smart backtracking algorithm

*5 Standard configuration. Different conditions under reques, please consult TrinaTracker